

EYP-DFB-0767-00050-1500-BFW01-000x


Revision 0.90

31.10.2016

SINGLE FREQUENCY LASER DIODES Distributed Feedback Laser

General Product Information

Product	Application
767 nm DFB Laser with hermetic Butterfly Housing	Spectroscopy
Monitor Diode, Thermoelectric Cooler and Thermistor	Metrology
Collimated beam	K Spectroscopy (Variant ...-0005)
ROHS compliant	



Absolute Maximum Ratings

Parameter	Symbol	Unit	min	typ	max
Storage Temperature	T_S	°C	-40		85
Operational Temperature at Case	T_C	°C	-40		85
Operational Temperature at Laser Chip	T_{LD}	°C	10		50
Forward Current	I_F	mA			130
Reverse Voltage	V_R	V			2
Output Power	P_{opt}	mW			60
TEC Current	I_{TEC}	A			1.8
TEC Voltage	V_{TEC}	V			2.8

Stress in excess of the Absolute Maximum Ratings can cause permanent damage to the device.

Recommended Operational Conditions

Parameter	Symbol	Unit	min	typ	max
Operational Temperature at Case	T_C	°C	-20		65
Operational Temperature at Laser Chip	T_{LD}	°C	15		35
Forward Current	I_F	mA			120
Output Power	P_{opt}	mW	10		50

Measurement Conditions / Comments

measured by integrated Thermistor

Characteristics at $T_{LD} = 25\text{ °C}$ at Begin Of Life

Parameter	Symbol	Unit	min	typ	max
Center Wavelength	λ_C	nm	766	767	768
Tuning Range by Temperature	$\Delta\lambda_T$	nm		1.2	
Spectral Width (FWHM)	$\Delta\nu$	MHz		2	
Temperature Coefficient of Wavelength	$d\lambda / dT$	nm / K		0.06	
Current Coefficient of Wavelength	$d\lambda / dI$	nm / mA		0.003	
Output Power @ $I_F = 120\text{ mA}$	P_{opt}	mW	50		

Measurement Conditions / Comments

see images on page 4

see also "Mode-hop free Operating Range" (p.2)

EYP-DFB-0767-00050-1500-BFW01-000x

Revision 0.90

31.10.2016

SINGLE FREQUENCY LASER DIODES Distributed Feedback Laser



Characteristics at $T_{amb} = 25\text{ °C}$ at Begin Of Life cont'd

Parameter	Symbol	Unit	min	typ	max
Slope Efficiency	η	W / A	0.6	0.9	1.1
Threshold Current	I_{th}	mA			70
Divergence parallel ($1/e^2$)	$\Theta_{ }$	°		0.1	
Divergence perpendicular ($1/e^2$)	Θ_{\perp}	°		0.1	
Beam Diameter ($1/e^2$)	$d_{ }$	mm		1.0	1.2
Beam Diameter ($1/e^2$)	d_{\perp}	mm		0.8	1.2
Degree of Polarization	DOP	%		90	
Sidemode Suppression Ratio	SMSR	dB	30	50	
Mode-hop free Operating Range (SMSR > 30 dB)					
▶ Variant 0	T_{LD}	° C		25	
	P_{opt}	mW		50	
▶ Variant 2	T_{LD}	° C	15		35
	P_{opt}	mW	10		50
▶ Variant 5	λ_c	nm		766.70	
	P_{opt}	mW		50	

Measurement Conditions / Comments

parallel to the base plate of the housing (see p. 3)
 perpendicular to base plate of the housing (see p. 3)
 parallel to the base plate of the housing (see p. 3)
 perpendicular to base plate of the housing (see p. 3)
 $P_{opt} = 50\text{ mW}$; E field perpendicular to the base plate
 $P_{opt} = 50\text{ mW}$
 see order code scheme on p. 5

wavelength reached within $T_{LD} = 15\text{ °}$ and 35 ° C

Monitor Diode


Parameter	Symbol	Unit	min	typ	max
Monitor Detector Responsivity	I_{mon}/P_{opt}	$\mu\text{A}/\text{mW}$	2		40

Measurement Conditions / Comments


Reverse Voltage $U_{R,MD} = 5\text{ V}$

Typical Measurement Results

Output Power vs. Current



Spectra at Specified Optical Output Power




Performance figures, data and any illustrative material provided in this specification are typical and must be specifically confirmed in writing by eagleyard Photonics before they become applicable to any particular order or contract. In accordance with the eagleyard Photonics policy of continuous improvement specifications may change without notice.

EYP-DFB-0767-00050-1500-BFW01-000x

Revision 0.90

31.10.2016

SINGLE FREQUENCY LASER DIODES Distributed Feedback Laser



Thermoelectric Cooler

Parameter	Symbol	Unit	min	typ	max
Current	I_{TEC}	A		0.4	
Voltage	U_{TEC}	V		0.8	
Power Dissipation (total loss at case)	P_{loss}	W		0.4	
Temperature Difference	ΔT	K			50

Measurement Conditions / Comments

 $P_{opt} = 50 \text{ mW}, \Delta T = 20 \text{ K}$
 $P_{opt} = 50 \text{ mW}, \Delta T = 20 \text{ K}$
 $P_{opt} = 50 \text{ mW}, \Delta T = 20 \text{ K}$
 $P_{opt} = 50 \text{ mW}, \Delta T = |T_{case} - T_{LD}|$

Thermistor (Standard NTC Type)

Parameter	Symbol	Unit	min	typ	max
Resistance	R	$k\Omega$		10	
Beta Coefficient	β			3892	
Steinhart & Hart Coefficient	A			1.1293×10^{-3}	
Steinhart & Hart Coefficient	B			2.3410×10^{-4}	
Steinhart & Hart Coefficient	C			8.7755×10^{-8}	

Measurement Conditions / Comments

 $T = 25^\circ \text{C}$
 $R_1 / R_2 = e^{\beta(1/T_1 - 1/T_2)}$ at $T = 0^\circ \dots 50^\circ \text{C}$
 $1/T = A + B(\ln R) + C(\ln R)^3$

T: temperature in Kelvin

R: resistance at T im Ohm

EYP-DFB-0767-00050-1500-BFW01-000x

Revision 0.90

31.10.2016

SINGLE FREQUENCY LASER DIODES Distributed Feedback Laser



Package Dimensions

Parameter	Symbol	Unit	min	typ	max
Emission Plane	h_{EP}	mm		4.9	





Measurement Conditions / Comments

Package Pinout

1	Thermoelectric Cooler (+)	14	Thermoelectric Cooler (-)
2	Thermistor	13	Case
3	Photodiode (Anode)	12	not connected
4	Photodiode (Cathode)	11	Laser Diode (Cathode)
5	Thermistor	10	Laser Diode (Anode)
6	not connected	9	not connected
7	not connected	8	not connected

Measurement Conditions / Comments

Package Drawings



AIZ-15-0729-0947A

EYP-DFB-0767-00050-1500-BFW01-000x

Revision 0.90

31.10.2016

SINGLE FREQUENCY LASER DIODES Distributed Feedback Laser

Order Code Scheme

x is a wildcard representing the different variants of the laser. Please select.

Mode-hop free Operating Range (Minimum Side Mode Suppression Ratio > 30 dB)

$T_{LD} = 25\text{ °C}$	$P_{opt} = 50\text{ mW}$	(Variant 0)
$T_{LD} = 15 \dots 35\text{ °C}$;	$P_{opt} = 10 \dots 50\text{ mW}$	(Variant 2)
$\lambda_c = 766.70\text{ nm}$	$P_{opt} = 50\text{ mW}$	(Variant 5)

EYP-DFB-0767-00050-1500-BFW01- 0 0 0 x

0
2
5



Unpacking, Installation and Laser Safety

Unpacking the laser diodes should only be done at electrostatic safe workstations (EPA). Though protection against electro static discharge (ESD) is implemented in the laser package, charges may occur at surfaces. Please store this product in its original package at a dry, clean place until final use. During device installation, ESD protection has to be maintained.

The DFB diode type is known to be sensitive against optical feedback, so an optical isolator may be required in some cases. Operating at moderate temperatures on a proper metal heat sinks will contribute to stable operation and a long lifetime of the diode.

The laser emission from this diode is close to the invisible infrared region of the electromagnetic spectrum. Avoid direct and/or indirect exposure to the free running beam. Collimating the free running beam with optics as common in optical instruments will increase threat to the human eye.

Each laser diode will come with an individual test protocol verifying the parameters given in this document.



Ordering Information:

800 Village Walk #316
Guilford, CT 06437
Ph: 203-401-8093

Email orders to: sales@xsoptix.com
Fax orders to: 800-878-7282