



**FEATURES**

- Wide bandwidth
- X-cut for high stability
- Low insertion loss

**APPLICATIONS**

- QPSK, QAM, OFDM

**RELATED EQUIPMENTS**

- Analog driver DR-AN
- MBC-IQ Automatic Bias Controller
- ModBox-IQ

The iXblue MXIQ-LN-30 is a wide bandwidth, low insertion loss Dual Parallel Mach-Zehnder Modulator. iXblue proprietary “Magic Junction” (patent n° US2008193077) confers it an unmatched low insertion loss, and its X-cut design guarantees high stability and zero chirp in a wide range of operational conditions.

The iXblue MXIQ-LN-30 modulator is a key device dedicated to complex modulation scheme such as QPSK, QAM and OFDM up to 56 Gbaud.

**MXIQ-LN-30 Performance Highlights**

Parameter	Min	Typ	Max	Unit
Operating wavelength	1530	1550	1580	nm
Insertion loss	-	5	7	dB
Electro-optical bandwidth	25	30	-	GHz

Specifications given at 25 °C, 1550 nm

**Ordering Information:**



800 Village Walk #316  
Guilford, CT 06437  
Ph: 203-401-8093

Email orders to: [sales@xsoptix.com](mailto:sales@xsoptix.com)  
Fax orders to: 800-878-7282

### Electrical Characteristics

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Electro-optic bandwidth	$S_{21}$	RF electrodes, from 2 GHz	25	30	-	GHz
Ripple $S_{21}$	$\Delta S_{21}$	RF electrodes	-	0.5	1	dB
Electrical return loss	$S_{11}$	RF electrodes, 0 - 25 GHz	-	-12	-10	dB
$V_{\pi}$ RF @ 50 kHz	$V_{\pi RF_{50kHz}}$	RF <sub>1</sub> & RF <sub>2</sub> electrodes	-	5.5	7	V
$V_{\pi}$ DC <sub>1,2</sub> electrodes	$V_{\pi DC_{1,2}}$	DC <sub>1</sub> & DC <sub>2</sub> electrodes	-	7	7.5	V
$V_{\pi}$ DC <sub>3</sub> electrodes	$V_{\pi DC_3}$	DC <sub>3</sub> electrodes	-	7.5	8.5	V
Impedance matching	$Z_{in-RF}$	-	-	50	-	$\Omega$
DC input impedance	$Z_{in-DC}$	-	1	-	-	M $\Omega$

### Optical Characteristics

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Crystal	-	-	Lithium Niobate X-Cut Y-Prop			
Operating wavelength	$\lambda$	-	1530	1550	1580	nm
Insertion loss	IL	Without connectors	-	5	7	dB
Optical return loss	ORL	-	-40	-45	-40	dB
Chirp	$\alpha$	-	-0.1	0	-0.1	-


All specifications given at 25°C, 1550 nm, unless differently specified

### Absolute Maximum Ratings


Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. These are absolute stress ratings only. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of the data sheet. Exposure to absolute maximum ratings for extended periods can adversely affect device reliability.

Parameter	Symbol	Min	Max	Unit
RF input power	$EP_{in}$	-	28	dBm
Bias voltage	$V_{bias}$	-20	+20	V
Optical input power	$OP_{in}$	-	20	dBm
Operating temperature	OT	0	+70	°C
Storage temperature	ST	-40	+85	°C


Typical Curve  $S_{21}$  &  $S_{11}$  from RF<sub>1</sub> Electrode



Typical Curve  $S_{21}$  &  $S_{11}$  from RF<sub>2</sub> Electrode



**Mechanical Diagram and Pinout**  
All measurements in mm



Port	Function	Note
IN / OUT	Optical input port / Optical output port	Polarization maintaining 1550 nm Corning PM 15-U25D length: 1.5 meter, buffer diameter: 900 μm
1 / 2	RF <sub>1</sub> input port / RF <sub>2</sub> input port	Wiltron female K (SMA compatible)
3	Ground	Pin feed through diameter 1.0 mm
4 / 5 / 6	DC <sub>2</sub> / DC <sub>1</sub> / DC <sub>3</sub>	Pin feed through diameter 1.0 mm
7 / 8	Photodiode 1 cathode / anode	Pin feed through diameter 1.0 mm
9 / 10	Photodiode 2 cathode / anode	Pin feed through diameter 1.0 mm

**Ordering information**

**MXIQ-LN-30-PD-Y-Z-AB-CD**

Y = Input fiber : P Polarisation maintening  
 Z = Input fiber : P Polarisation maintening S Standard single mode  
 AB = Output connector : 00 bare fiber FA FC/APC FC FC/SPC  
 CD = Output connector : 00 bare fiber FA FC/APC FC FC/SPC  
 Note : optical

**About us**

ixBlue Photonics produces specialty optical fibers and Bragg gratings based fiber optics components and provides optical modulation solutions based on the company lithium niobate (LiNbO<sub>3</sub>) modulators and RF electronic modules.

ixBlue Photonics serves a wide range of industries: sensing and instruments, defense, telecommunications, space and fiber lasers as well as research laboratories all over the world.