

Model Number: **ASE-C0-RS-35.5-NO-FCA**

Product Code: **1709**

Micro Processor Controlled

Amplified Spontaneous Emission Source



Specifications:

Parameters	Specifications
Wavelength Range	1540 – 1565nm
Gain Flattening Filter	Not included
Output Power	+35.5 dBm
Optical Output Fiber	900um loose tube, FC/APC, red, 1 meter, SMF-28
Output Power Monitoring Range	+23 to +36 dBm
Output Power Measurement Accuracy	≤ +/- 0.3 dB, 1550 nm
Polarization Dependence of Output Power	≤ 0.3 dB
Control and Communication Interface	RS-232, RS232 Voltage Level
Dimension	200 x 100 x 49 mm
Power Input	+24 VDC +/- 5%
Electrical Interface Connector	PN: 173-E25-113R001 Male 25-PIN
Operational Case Temperature Range	0 to +60 °C
Mode of Operation	AOPC (constant output power control), ACC (constant pump current control)

Electrical connector:

Part number: 173-E25-113R001

Pin No.	Description	Pin No.	Description
1	24V Vin	14	24V Vin
2	24V Vin	15	24V Vin
3	GROUND	16	GROUND
4	GROUND	17	GROUND
5	COMMON ALARM OUT	18	CUSTOMER LASER EN/DIS
6	BOOSTER CURRENT ALARM OUT	19	CASE-INPUT POWER ALARM OUT
7	GROUND	20	LASER STATUS OUT
8	GROUND	21	GROUND
9	GROUND	22	RS232 RX
10	RS232 TX	23	GROUND
11	GROUND	24	ANALOG GROUND
12	ANALOG GROUND	25	BOOSTER ANALOG CURRENT SET
13	CASE TEMP OUT		

Ordering Information:



800 Village Walk #316
 Guilford, CT 06437
 Ph: 203-401-8093

Email orders to: sales@xsoptix.com
 Fax orders to: 800-878-7282

