


YTTERBIUM DOPED FIBER LASER

Model Number: **YDFL-NANO-1060-100-50-1.5-COL**

Product Code: **1502**

Micro Processor Controlled


Nanosecond Fiber Laser Module



Specifications:

Parameters	Specifications
Center Wavelength	1060 nm typical
Pulse Width	70 – 100 ns
Energy Per Pulse	Up to 50 μ J
Pulse Repetition Rate	30 kHz
Output Power	1.5 W
Optical Output	3.5 mm beam diameter
Output Beam Divergence	0.5 mrad typical
Timing Jitter	\leq 2 ns, rising edge of the TTL trigger to the Laser Output Pulse
Control and Communication Interface	RS-232, RS-232 voltage level
Dimension	158 x 120 x 25 mm
Power Input	+24 VDC +/- 5%
Electrical Interface Connector	PN: MD25M2000/AA
Operational Case Temperature Range	-5 to +60 $^{\circ}$ C
Mode of Operation	ACC (constant pump current control)

Ordering Information:



800 Village Walk #316
 Guilford, CT 06437
 Ph: 203-401-8093

Email orders to: sales@xsoptix.com
 Fax orders to: 800-878-7282

YTTERBIUM DOPED FIBER LASER



Top trace: external trigger Bottom trace: laser output pulse

Electrical connector:

Part number: MD25M2000/AA

Pin No.	Description	Pin No.	Description
1	PUMP ENABLE/DISABLE	14	RS232 RX
2	LASER STATUS	15	RGND
3		16	PA IBIAS ALARM
4	CUSTOMER SIGNAL	17	MMBA IBIAS ALARM
5	GROUND	18	CASE TEMP ALARM
6	CASE TEMP OUT	19	TRIG ALARM
7	MECH ENCLOSURE	20	COM ALARM
8	AGND	21	+24 VDC
9	MM IBIAS OUT	22	+24V DC
10	PRE-IBIAS OUT	23	GROUND
11	BURST INP	24	GROUND
12	NC	25	
13	RS232 TX		

