

# YTTERBIUM DOPED FIBER LASER

Model Number: **YDFL-NANO-1064-2-10-1-FCA**

Product Code: **1502**

**Micro Processor Controlled**

**Nanosecond Fiber Laser Module**



## Specifications:

Parameters	Specifications
Center Wavelength	1064 nm typical
Pulse Width	2 – 3 ns
Energy Per Pulse	Up to 10 μ J
Pulse Repetition Rate	100 – 250 kHz
Output Power	1.0 W
Optical Output	Cable with FC/APC, 12/125um core / cladding NA = 0.07
Timing Jitter	≤ 2 ns, rising edge of the TTL trigger to the Laser Output Pulse
Control and Communication Interface	RS-232, RS-232 voltage level
Dimension	158 x 120 x 25 mm
Power Input	+24 VDC +/- 5%
Electrical Interface Connector	PN: MD25M2000/AA
Operational Case Temperature Range	-5 to +60 °C
Mode of Operation	ACC (constant pump current control)


*Ordering Information:*



800 Village Walk #316  
 Guilford, CT 06437  
 Ph: 203-401-8093

Email orders to: [sales@xsoptix.com](mailto:sales@xsoptix.com)  
 Fax orders to: 800-878-7282

# YTTERBIUM DOPED FIBER LASER



Typical Laser Pulse Shape

**Electrical connector:**

Part number: MD25M2000/AA

Pin No.	Description	Pin No.	Description
1	PUMP ENABLE/DISABLE	14	RS232 RX
2	LASER STATUS	15	RGND
3		16	PA IBIAS ALARM
4	CUSTOMER SIGNAL	17	MMBA IBIAS ALARM
5	GROUND	18	CASE TEMP ALARM
6	CASE TEMP OUT	19	TRIG ALARM
7	MECH ENCLOSURE	20	COM ALARM
8	AGND	21	+24 VDC
9	MM IBIAS OUT	22	+24V DC
10	PRE-IBIAS OUT	23	GROUND
11	BURST INP	24	GROUND
12	NC	25	
13	RS232 TX		

